

BOGE Model	Max. pressure**		Effective free air delivery*		Motor power		Dimensions W x D x H mm	Weight kg
	bar	psig	m ³ /min	cfm	kW	HP		
C 4	8	115	0.427	15	3.0	4.0	480 x 920 x 960	190
C 4	10	150	0.340	12	3.0	4.0	480 x 920 x 960	190
C 4	13	190	0.280	10	3.0	4.0	480 x 920 x 960	190
C 5	8	115	0.630	22	4.0	5.5	480 x 920 x 960	195
C 5	10	150	0.545	19	4.0	5.5	480 x 920 x 960	195
C 5	13	190	0.440	15	4.0	5.5	480 x 920 x 960	195
C 7	8	115	0.900	32	5.5	7.5	480 x 920 x 960	210
C 7	10	150	0.770	27	5.5	7.5	480 x 920 x 960	210
C 7	13	190	0.642	23	5.5	7.5	480 x 920 x 960	210
C 9	8	115	1.200	42	7.5	10.0	480 x 1000 x 1240	215
C 9	10	150	1.100	39	7.5	10.0	480 x 1000 x 1240	215
C 9	13	190	0.900	32	7.5	10.0	480 x 1000 x 1240	215
C 4 D	8	115	0.427	15	3.0	4.0	480 x 1000 x 1240	210
C 4 D	10	150	0.340	12	3.0	4.0	480 x 1000 x 1240	210
C 4 D	13	190	0.280	10	3.0	4.0	480 x 1000 x 1240	210
C 5 D	8	115	0.630	22	4.0	5.5	480 x 1000 x 1240	215
C 5 D	10	150	0.545	19	4.0	5.5	480 x 1000 x 1240	215
C 5 D	13	190	0.440	15	4.0	5.5	480 x 1000 x 1240	215
C 7 D	8	115	0.900	32	5.5	7.5	480 x 1000 x 1240	230
C 7 D	10	150	0.770	27	5.5	7.5	480 x 1000 x 1240	230
C 7 D	13	190	0.642	23	5.5	7.5	480 x 1000 x 1240	230
C 9 D	8	115	1.200	42	7.5	10.0	480 x 1000 x 1240	235
C 9 D	10	150	1.100	39	7.5	10.0	480 x 1000 x 1240	235
C 9 D	13	190	0.900	32	7.5	10.0	480 x 1000 x 1240	235

* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 59 dB(A) according to DIN EN ISO 2151:2009.

** Max. pressure of the compressor