

BOGE Model	Max. pressure		Effective free air delivery*		Motor power		Dimensions silenced	Dimensions super-silenced/ with radial fan	Com-pressed air outlet	Weight silenced/ with radial fan	Weight super-silenced
	bar	psig	m ³ /min	cfm	kW	HP	W x D x H in mm	W x D x H in mm		kg	kg
SLF 221	8	115	6.46-28.21	228- 996	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
	10	150	6.18-25.06	218- 885	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
	13	190	5.46-20.36	193- 719	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
SLF 271	8	115	6.46-34.70	228-1225	200	270	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4700/ –	4800
	10	150	6.18-30.50	218-1077	200	270	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4700/ –	4800
	13	190	5.46-24.73	193- 873	200	270	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4700/ –	4800

* Free air delivery for the complete package in accordance with ISO 1217, Appendix E, at 20°C ambient temperature and maximum pressure. Emitted sound pressure values from 70 dB(A) according to DIN EN ISO 2151:2009

** Max. pressure of the compressor